

Description: 18 AWG 2/C CL2P Thermostat
Compliance: UL Standard 13; NEC Article 725

Construction:

Conductors 18 AWG Solid Bare Copper
No. of Conductors 2

Insulation

Type Plenum PVC
Color Red,Wht
Thickness 0.006" nom.
Diameter 0.052" nom.

Jacket

Type Plenum PVC
Color Beige
Thickness 0.015" nom.
Diameter 0.136" nom.

Legend (Ink Print)

HONEYWELL THERMOSTAT CABLE P/N 4760 2C18 3038058 (ETL) CL2P (RoHS)
C(ETL) FT6 w/o# XXXXXX-XXXXXX XXXXXFT

Packaging

4 x 500' Reels

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 39 pf/ft nom.
Characteristic Impedance 55 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating UL 910, NFPA 262, C(UL) FT6

Description: 18 AWG 3/C CL2P Thermostat
Compliance: UL Standard 13; NEC Article 725

Construction:

Conductors 18 AWG Solid Bare Copper
No. of Conductors 3

Insulation

Type Plenum PVC
Color Red, Wht, Grn
Thickness 0.006" nom.
Diameter 0.052" nom.

Jacket

Type Plenum PVC
Color Beige
Thickness 0.015" nom.
Diameter 0.144" nom.
Legend (Ink Print)

HONEYWELL THERMOSTAT CABLE P/N 4761 3C18 3038058 (ETL) CL2P (RoHS)
C(ETL) FT6 w/o# XXXXXX-XXXXXX XXXXXFT

Packaging 4 x 500' Reels

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 39 pf/ft nom.
Characteristic Impedance 55 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating UL 910, NFPA 262, C(UL) FT6

Description: 18 AWG 4/C CL2P Thermostat
Compliance: UL Standard 13; NEC Article 725

Construction:

Conductors 18 AWG Solid Bare Copper
No. of Conductors 4
Assembly Tubed jacket over cabled insulated conductors

Insulation

Type Plenum PVC
Color Red,Wht,Grn,Blu
Thickness 0.006" nom.
Diameter 0.052" nom.
Cable Lay Length 5.0" nom

Jacket

Type Plenum PVC
Color Beige
Thickness 0.015" nom.
Diameter 0.157" nom.

Legend (Ink Print)

HONEYWELL THERMOSTAT CABLE P/N 4762 4C18 3038058 (ETL) CL2P (RoHS)
C(ETL) FT6 w/o# XXXXXX-XXXXXX XXXXXFT

Packaging 4 x 250' Reels

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 39 pf/ft nom.
Characteristic Impedance 55 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating UL 910, NFPA 262, C(UL) FT6

Description: 18 AWG 5/C CL2P Thermostat
Compliance: UL Standard 13; NEC Article 725

Construction:

Conductors 18 AWG Solid Bare Copper
No. of Conductors 5

Insulation

Type Plenum PVC
Color Red, Wht, Grn, Blu, Ylw
Thickness 0.006" nom.
Diameter 0.052" nom.
Cable Lay Length 5.25" nom

Jacket

Type Plenum PVC
Color Beige
Thickness 0.015" nom.
Diameter 0.172" nom.

Legend (Ink Print)

HONEYWELL THERMOSTAT CABLE P/N 4763 5C18 3038058 (ETL) CL2P (RoHS)
C(UL) FT6 w/o# XXXXXX-XXXXXX XXXXXFT

Packaging

4 x 250' Reels

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 39 pf/ft nom.
Characteristic Impedance 55 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating UL 910, NFPA 262, C(UL) FT6

Description: 18 AWG 6/C CL2P Thermostat
Compliance: UL Standard 13; NEC Article 725

Construction:

Conductors 18 AWG Solid Bare Copper
No. of Conductors 6
Assembly Tubed jacket over cabled insulated conductors

Insulation

Type Plenum PVC
Color Red, Wht, Grn, Blu, Ylw, Brn
Thickness 0.006" nom.
Diameter 0.052" nom.
Cable Lay Length 5.5" nom

Jacket

Type Plenum PVC
Color Beige
Thickness 0.015" nom.
Diameter 0.188" nom.
Legend (Ink Print)

HONEYWELL THERMOSTAT CABLE P/N 4764 6C18 3038058 (ETL) CL2P (RoHS) C(UL)
FT6 w/o# XXXXXX-XXXXXX XXXXXFT

Packaging 4 x 250' Reels, or 1 x 500' Reel or Box

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 39 pf/ft nom.
Characteristic Impedance 55 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating UL 910, NFPA 262, C(UL) FT6

Description: 18 AWG 8/C CL2P Thermostat
Compliance: UL Standard 13; NEC Article 725

Construction:

Conductors 18 AWG Solid Bare Copper
No. of Conductors 8
Assembly Tubed jacket over cabled insulated conductors

Insulation

Type Plenum PVC
Color Red, Wht, Grn, Blu, Ylw, Brn, Org, Blk
Thickness 0.006" nom.
Diameter 0.052" nom.
Cable Lay Length 6.0" nom

Jacket

Type Plenum PVC
Color Beige
Thickness 0.015" nom.
Diameter 0.204" nom.
Legend (Ink Print)

HONEYWELL THERMOSTAT CABLE P/N 4766 8C18 3038058 (ETL) CL2P (RoHS)
C(UL) FT6 w/o# XXXXXX-XXXXXX XXXXXFT

Packaging

4 x 250' Reels, or 1 x 500' Reel or Box

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 39 pf/ft nom.
Characteristic Impedance 55 Ohms nom.
DC Resistance 6.5 Ohms/M' at 20°C
Flame Rating UL 910, NFPA 262, C(UL) FT6