

14/7 STRANDED THHN 600V TRAY CABLE P/N 1073

Description:

AWG 14/7 stranded bare copper conductors, (THHN) PVC/nylon, Sunlight Resistance, RoHS compliant PVC jacketed cable, 600V Direct Burial listed by UL.

Physical Information:

	<u>Conductor</u>
Type:	14 AWG STR 19/.0147" Bare Copper
Diameter:	0.0735" nom.
	<u>Insulation</u>
Type:	PVC w/Nylon
Thickness:	PVC – 0.015" nom Nylon – 0.005" nom
Color:	Black, White, Red, Green, Brown, Blue, Orange, cabled with poly fillers.
	<u>Jacket</u>
Type:	PVC
Color:	Black
Thickness:	0.055" nom.
Diameter:	0.460" nom.

Print Legend: HONEYWELL 14/7C POWER & CONTROL CABLE TYPE TC UL 1277 EXXXXXX
DIRECT BURIAL SUN RES (RoHS) W/O# XXXXXX-XXXXXX XXXXX FT

Packaging: 250-ft wooden Reel, 150 lbs capacity
5 x 50-ft coils in box

	<u>Rating</u>
Voltage:	600 V
Temperature:	-20 to 90 C
Listing:	Tray Cable - UL 1277, Direct Burial, Sunlight Resistance



Your Mini-Split Cable Solution!

Honeywell has the mini-split cables you need, from low-voltage control to high-voltage power and control. Our selection includes various lengths, including convenient job sized 50' coils. The 50' coils save you time and money by simplifying job pricing, ordering, and inventory maintenance. Just load your truck each day with a 50' coil for each mini-split unit.

Cable Description	Part #
18/2 Stranded CM/CL2	1118
18/4 Stranded CM/CL2	1119
16/2 Stranded CM/CL2	1125
16/4 Stranded CM/CL2	1126
18/2 Stranded Shielded CM/CL2	1214
18/4 Stranded Shielded CM/CL2	1215
16/2 Stranded Shielded CM/CL2	1221
16/4 Stranded Shielded CM/CL2	1222
16/4 Stranded THHN 600V	1068
14/4 Stranded THHN 600V	1070
14/7 Stranded THHN 600V	1073



Convenient Job Sized 50' Coil

Cables cross referenced on other side by mini-split manufacturer.

Mini Split Brand	Models	Cable Description	Part #
Carrier®	RASLK/RASLA, 40GXM/38GXM	14/4 Stranded THHN 600V	1070
	40QNC/38HDF, 40KMC/38HDF	18/2 Stranded CM/CL2 (up to 50 feet)	1118
		16/2 Stranded CM/CL2 (up to 200 feet)	1125
	40GXQ/38GXQ, 40GXC/38GXC, 40MVQ/38MVQ, 40MVC/38MVC	18/4 Stranded CM/CL2 (up to 50 feet)	1119
		16/4 Stranded CM/CL2 (up to 100 feet)	1126
Daikin		14/4 Stranded THHN 600V	1070
Environair	Cooling Only Models	14/4 Stranded THHN 600V	1070
	Heating Models	14/7 Stranded THHN 600V	1073
Friedrich®		14/4 Stranded THHN 600V	1070
Fujitsu®		14/4 Stranded THHN 600V	1070
Gree		14/4 Stranded THHN 600V	1070
Grunaire		14/4 Stranded THHN 600V	1070
Heat Controller Inc.		14/4 Stranded THHN 600V	1070
LG®		14/4 Stranded THHN 600V	1070
Mitsubishi®	M-Series	14/4 Stranded THHN 600V	1070
	P-Series	16/4 Stranded THHN 600V	1068
	City-Multi Units	16/2 Stranded CM/CL2	1125
NORDYNE	IQ Drive	T-Stat: 18/4 Stranded OAS CM/CL2	1215
		Communication: 18/3 Stranded Shielded CM/CL2	1228
		Power: 18/2 Stranded CM/CL2	1118
Panasonic		14/4 Stranded THHN 600V	1070
Quietside®	Single & Multizone Inverter	14/4 Stranded THHN 600V	1070
	Single-Zone Rotary Models	14/7 Stranded THHN 600V	1073
Samsung®		Comm: 16/2 Stranded Shielded CM/CL2	1221
York®		14/4 Stranded THHN 600V	1070

All trademarks are property of their respective owners.



Download our FREE HVAC “We’ve Got a Cable for That” mobile app and keep wire selection at your fingertips. Visit www.honeywellcable.com and follow the links to download our FREE app.

As always, wire from Honeywell Genesis Series Cable is the ONLY wire qualified for Honeywell Contractor PRO™ points. Not signed up for Contractor PRO? Go to www.contractorpro.com and sign-up in less than 15 minutes. Begin earning points for the wire you buy every day.

For more information:

www.honeywellcable.com

Automation and Control Solutions

Honeywell Genesis® Series Cable
 7701 95th Street
 Pleasant Prairie, WI 53158-2716
 800.222.0060
www.honeywell.com

