

# 1520CW&reg

## FOIL INSULATION TAPE

Venture Tape 1520CW COLD WEATHER FOIL is an annealed aluminum foil coated with Ventures CW&reg; cold weather solvent acrylic pressure sensitive adhesive. The malleable foil applies easily to both fibrous and sheet metal ducts and conforms to irregular surfaces. Venture Tape 1520CW excels in demanding temperature and humidity applications and provides superior performance and durability over a wide range of environmental conditions.

### Features & Benefits

- UL723 Listed (5/10 Flame/Smoke rating)

Name	Imperial Typical Value	Typical Value (Metric)
Thickness Carrier	2.0 mils	50.8 $\hat{I}$ ¼m
Thickness Adhesive Exposed	1.25 mils	31.8 $\hat{I}$ ¼m
Thickness Liner	3.0 mils	76.2 $\hat{I}$ ¼m
Peel Adhesion Exposed	96 oz/inch width	26.7 N/25 mm
Shear Strength Exposed	>168 hrs	>168 hrs
Tensile Strength	27 lbs/inch width	120 N/25 mm width
Elongation	4.4%	4.4%
Minimum Appl	-25 degrees F	-32 degrees C
Maximum Use Temp	260 degrees F	127 degrees C

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Contact Venture Tape today for a complete list of products or a free sample  
Toll Free North America 800-343-1076  
From United Kingdom 0-800-962-957  
From Australia 1-800-122-797  
[www.venturetape.com](http://www.venturetape.com)  
[www.boma.it](http://www.boma.it)



**USA**  
Venture Tape Corp.  
30 Commerce Road  
Rockland, MA 02370  
781-331-5900  
FAX 781-871-0065  
[www.venturetape.com](http://www.venturetape.com)

**Europe - Venture Tape**  
Venture Tape Europe Corp.  
Units 5 - 6, Faraday Close,  
Drayton Fields, Daventry,  
Northamptonshire, England NN11 8RD  
(0) 1327 876555  
FAX (0) 1327 876444

**Australasia**  
Venture Tape Australasia, Pty., Ltd.  
11B Production Drive  
Campbellfield, VIC 3061  
Australia  
(03) 9357 6025  
FAX (03) 9357 6045