

Description: 6 Conductor 18/20 AWG Solid Unshielded Thermostat Cable Class 2 (CL2)  
Compliance: UL Standard 13; NEC Article 725

**Construction:**

Conductors 18 & 20 AWG Solid Bare Copper  
No. of Conductors 1 x 18 AWG, 5 x 20 AWG

Insulation

Type Polypropylene  
Thickness 0.006" nom  
Color 18 AWG – Red; 20 AWG - Wht, Grn, Blu, Ylw, Brn  
Diameter 18 AWG - 0.052"; 20 AWG - 0.043" nom.

Jacket

Type PVC  
Color Brown  
Thickness 0.015" nom.  
Diameter 0.168" nom.

Legend (Ink Print)

HONEYWELL THERMOSTAT CABLE P/N 6714 1C18 + 5C20 3038058 (ETL) CL2  
SUN RES (RoHS) w/o# XXXXX-XXXXXX XXXXXFT

**Packaging**

250 ft Speed Bag or 4 x 250 ft reels

**Properties**

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 22 pF/ft nom.  
DC Resistance 20 AWG - 10.3 Ohms/M' at 20°C  
18 AWG – 6.5 Ohms/M' at 20°C  
Flame Rating UL 1685 Vertical Tray  
Country of Origin USA