



Mini Condensate Pump

Model: MS601UL

Includes: Pump with mounting pad, Condensate reservoir, breather tube, 1/2" drain inlet adapter, 5' of 1/4" ID tubing



Application: Mini Split system up to 36,000 BTU



Power Supply	120V 60Hz 0.19 Amps
Water Temp Range	41°F - 140°F
Size Reservoir	4.3" L x 1.5" W x 1.6" H
Size Pump & pad	3.4" L x 2.8" W x 2.5" H
Inlet/ Outlet size	1/4" ID tubing
Switch	Single reed switch with on/off and safety (N.O.)

Pump & Switch Power cord	5'
Duty Cycle	50%
Flow rate @ 0' @20'	3.5 gph 2.3 gph Avg Performance
Max lift	65'
Max suction lift	12.9'



Mini Condensate Pump

Model: MS602ULC

Includes: Pump with mounting pad, Condensate reservoir, breather tube, 1/2" drain inlet adapter, 5' of 1/4" ID tubing



Applications: Mini Split systems up to 36,000 BTU



Power Supply	230V 50Hz 0.08 A 18 Watts 230V 60Hz 0.07 A 15 Watts
Water Temp range	41°F—140°F
Size Reservoir Size Pump & pad	4.3" x 1.5" x 1.6" 3.4" x 2.8" x 2.5"
Inlet/ Outlet size	1/4" ID tubing
Switch	Single reed switch with on/off and safety (N.O.)

Switch Power Cord	5'
Pump Power cord	5'
Duty Cycle	50%
Flow rate @ 0' @20'	3.5 gph 2.3 gph Average Performance
Max lift	65'
Max suction	12.9'