TECHNICAL SPECIFICATIONS



Stainless Steel Flexible Gas Connectors

(EFGC-012-YE Series)

EFGC-Series stainless steel flexible gas connector offer you a full spectrum of product varieties to fit your needs. Corrosion resistant stainless steel 304 tubing and zinc-plated steel fitting provide 100% quality you can trust. Safe-guard yellow epoxy coating provides extra protection from corrosion, chemical stains from common household products, and plumbing repair products.

FEATURES

- Flexible and durable with full spectrum of product varieties.
- 100% leak tested for quality and safety
- Uniform Safe-guard epoxy coating available in yellow and black color for corrosion resistance.

MATERIALS

Tubing	Stainless Steel 304 (ASTM A240)		
Coating	Ероху		
Fittings	Zinc-Plated Steel S45C		

SPECIFICATIONS

Rated Operating Temperature	-40°F to 150°F (-40°C to 65°C)			
Rated Pressure	0.5 psi			

DESIGN CERTIFICATIONS AND APPROVALS

- ANSI Z 21.24 / CSA 6.10 Gas Appliances
- ANSI Z 21.69 / CSA 6.16 Movable Gas Appliances
- ANSI Z 21.75 / CSA 6.27 Outdoor Gas Appliances & Manufactured Homes
- Commonwealth of Massachusetts Board of State Examiners (except 48", 60", 72")
- City of New York-MEA #376-92-M



CONNECTOR MINIMUM FLOW CAPACITY

Series	Nominal OD	Nominal ID	12"	18"	24"	30"	36"	48"	60"	72"
012	5/8"	1/2"	180,000	164,200	150,000	136,000	125,000	106,000	93,200	86,000

Job Name :	Engineer / Architect :		
Job Location :	Wholesaler:		
Submittal Date :	Contractor:		

