

ENAMEL SPRAY PAINT

Safety Data Sheet

Date of issue: 5/21/2015

Revision date: 1/27/2016

Supersedes: 5/21/2015

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : ENAMEL SPRAY PAINT
Product code : 423222
Type of product : Spraying paint (spray can)
Vaporizer : Aerosol
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

AKKİM YAPI KİMYASALLARI SANAYİ ve TİCARET A.Ş.
Yeşilbayır mahallesi Şimşir sokak No:22
34555 İSTANBUL - TURKEY
T +90 2127711371 - F +90 2127713888
info@akfix.com - www.akfix.com

1.4. Emergency telephone number

Emergency number : +90 2127711371 (9:00 am - 17:00 pm GMT+2)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixture/S

Aerosol, Category 1 H222;H229 On basis of test data
Serious eye damage/eye irritation, Category 2 H319 Calculation method
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336 Calculation method

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

acetone, propan-2-one, propanone

Hazard statements (CLP) :

H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

ENAMEL SPRAY PAINT Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/21/2015

Revision date: 1/27/2016

Supersedes: 5/21/2015

Version: 1.0

Precautionary statements (CLP)	: P102 - Keep out of reach of children P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P211 - Do not spray on an open flame or other ignition source P251 - Do not pierce or burn, even after use P261 - Avoid breathing spray P280 - Wear protective clothing, protective gloves P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone, propan-2-one, propanone	(CAS No) 67-64-1 (EC no) 200-662-2 (EC index no) 606-001-00-8 (REACH-no) 01-2119471330-49	25 - 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
dimethyl ether (Note U)	(CAS No) 115-10-6 (EC no) 204-065-8 (EC index no) 603-019-00-8 (REACH-no) 01-2119472128-37	20 - 25	Flam. Gas 1, H220 Press. Gas
n-butyl acetate	(CAS No) 123-86-4 (EC no) 204-658-1 (EC index no) 607-025-00-1 (REACH-no) 01-2119485493-29	12.5 - 20	Flam. Liq. 3, H226 STOT SE 3, H336
propane (Note U)	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5 (REACH-no) 01-2119486944-21	10 - 12.5	Flam. Gas 1, H220 Press. Gas
butane (Note C)(Note U)	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0 (REACH-no) 01-2119474691-32	5 - 10	Flam. Gas 1, H220 Press. Gas
2-methoxy-1-methylethyl acetate	(CAS No) 108-65-6 (EC no) 203-603-9 (EC index no) 607-195-00-7 (REACH-no) 01-2119475791-29	5 - 10	Flam. Liq. 3, H226
isobutane (Note C)(Note U)	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0 (REACH-no) 01-2119485395-27	2.5 - 10	Flam. Gas 1, H220
ethanol, ethyl alcohol	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5 (REACH-no) 01-2119457610-43	< 2.5	Flam. Liq. 2, H225

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U : When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Full text of H-statements: see section 16

ENAMEL SPRAY PAINT

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/21/2015

Revision date: 1/27/2016

Supersedes: 5/21/2015

Version: 1.0

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : Repeated exposure may cause skin dryness or cracking.
- Symptoms/injuries after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol.
- Explosion hazard : Pressurized container: May burst if heated.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Recover mechanically the product.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

ENAMEL SPRAY PAINT

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/21/2015

Revision date: 1/27/2016

Supersedes: 5/21/2015

Version: 1.0

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ENAMEL SPRAY PAINT		
EU	Local name	Acetone
EU	IOELV TWA (mg/m ³)	1210 mg/m ³
EU	IOELV TWA (ppm)	500 ppm
Austria	Local name	Aceton
Austria	MAK (mg/m ³)	1200 mg/m ³
Austria	MAK (ppm)	500 ppm
Austria	MAK Short time value (mg/m ³)	4800 mg/m ³
Austria	MAK Short time value (ppm)	2000 ppm
Belgium	Local name	Acétone
Belgium	Limit value (mg/m ³)	1210 mg/m ³
Belgium	Limit value (ppm)	500 ppm
Belgium	Short time value (mg/m ³)	2420 mg/m ³
Belgium	Short time value (ppm)	1000 ppm
Bulgaria	Local name	Ацетон*
Bulgaria	OEL TWA (mg/m ³)	600 mg/m ³
Bulgaria	OEL STEL (mg/m ³)	1400 mg/m ³
Croatia	Local name	Aceton
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	1210 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	500 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	3620 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	1500 ppm
Croatia	Naznake (HR)	F, Xi EU*
Czech Republic	Local name	Aceton
Czech Republic	Expoziční limity (PEL) (mg/m ³)	800 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	337 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	1500 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	632 ppm
Denmark	Local name	Acetone
Denmark	Grænseværdie (langvarig) (mg/m ³)	600 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	250 ppm
Denmark	Anmærkninger (DK)	E
Estonia	Local name	Atsetoon (2-propanoon)
Estonia	OEL TWA (mg/m ³)	1210 mg/m ³
Estonia	OEL TWA (ppm)	500 ppm
France	Local name	Acétone
France	VME (mg/m ³)	1210 mg/m ³
France	VME (ppm)	500 ppm
France	VLE (mg/m ³)	2420 mg/m ³
France	VLE (ppm)	1000 ppm
Germany	Local name	Aceton
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	1200 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	500 ppm
Germany	Remark (TRGS 900)	DFG,EU
Greece	OEL TWA (mg/m ³)	1780 mg/m ³
Greece	OEL STEL (mg/m ³)	3560 mg/m ³
Hungary	Local name	ACETON
Hungary	AK-érték	1210 mg/m ³

ENAMEL SPRAY PAINT

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/21/2015

Revision date: 1/27/2016

Supersedes: 5/21/2015

Version: 1.0

Hungary	CK-érték	2420 mg/m ³
Hungary	Megjegyzések (HU)	i; EU1
Ireland	Local name	Acetone
Ireland	OEL (8 hours ref) (mg/m ³)	1210 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	500 ppm
Ireland	Notes (IE)	IOELV
Italy	Local name	Acetone
Italy	OEL TWA (mg/m ³)	1210 mg/m ³
Italy	OEL TWA (ppm)	500 ppm
Latvia	Local name	Acetons (2-propanons, dimetilketons)
Latvia	OEL TWA (mg/m ³)	1210 mg/m ³
Latvia	OEL TWA (ppm)	500 ppm
Lithuania	Local name	Acetonas
Lithuania	IPRV (mg/m ³)	1210 mg/m ³
Lithuania	IPRV (ppm)	500 ppm
Lithuania	TPRV (mg/m ³)	2420 mg/m ³
Lithuania	TPRV (ppm)	1000 ppm
Luxembourg	Local name	Acétone
Luxembourg	OEL TWA (mg/m ³)	1210 mg/m ³
Luxembourg	OEL TWA (ppm)	500 ppm
Malta	Local name	Acetone
Malta	OEL TWA (mg/m ³)	1210 mg/m ³
Malta	OEL TWA (ppm)	500 ppm
Netherlands	Local name	Aceton
Netherlands	Grenswaarde TGG 8H (mg/m ³)	1210 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	2420 mg/m ³
Poland	Local name	Aceton
Poland	NDS (mg/m ³)	600 mg/m ³
Poland	NDSch (mg/m ³)	1800 mg/m ³
Portugal	Local name	Acetona
Portugal	OEL TWA (ppm)	500 ppm
Portugal	OEL STEL (ppm)	750 ppm
Romania	Local name	Acetona
Romania	OEL TWA (mg/m ³)	1210 mg/m ³
Romania	OEL TWA (ppm)	500 ppm
Slovenia	Local name	aceton
Slovenia	OEL TWA (mg/m ³)	1210 mg/m ³
Slovenia	OEL TWA (ppm)	500 ppm
Spain	Local name	Acetona
Spain	VLA-ED (mg/m ³)	1210 mg/m ³
Spain	VLA-ED (ppm)	500 ppm
Spain	Notes	VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento.) , VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
Sweden	Local name	Acetone
Sweden	nivågränsvärde (NVG) (mg/m ³)	600 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	250 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	1200 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	500 ppm

ENAMEL SPRAY PAINT

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/21/2015

Revision date: 1/27/2016

Supersedes: 5/21/2015

Version: 1.0

United Kingdom	Local name	Acetone
United Kingdom	WEL TWA (mg/m ³)	1210 mg/m ³
United Kingdom	WEL TWA (ppm)	500 ppm
United Kingdom	WEL STEL (mg/m ³)	3620 mg/m ³
United Kingdom	WEL STEL (ppm)	1500 ppm
Iceland	Local name	Aseton (2-própanón)
Iceland	OEL (8 hours ref) (mg/m ³)	600 mg/m ³
Iceland	OEL (8 hours ref) (ppm)	250 ppm
Norway	Local name	Aceton
Norway	Grenseverdier (AN) (mg/m ³)	295 mg/m ³
Norway	Grenseverdier (AN) (ppm)	125 ppm
Switzerland	Local name	Acétone
Switzerland	VME (mg/m ³)	1200 mg/m ³
Switzerland	VME (ppm)	500 ppm
Switzerland	VLE (mg/m ³)	2400 mg/m ³
Switzerland	VLE (ppm)	1000 ppm
Switzerland	Remark (CH)	4x15
Australia	Local name	Acetone
Australia	TWA (mg/m ³)	1185 mg/m ³
Australia	TWA (ppm)	500 ppm
Australia	STEL (mg/m ³)	2375 mg/m ³
Australia	STEL (ppm)	1000 ppm
USA - ACGIH	Local name	Acetone
USA - ACGIH	ACGIH TWA (ppm)	250 ppm
USA - ACGIH	ACGIH STEL (ppm)	500 ppm
USA - ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Liquid under pressure.
Colour	: white.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: 235 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapour pressure	: 8300 hPa
Relative vapour density at 20 °C	: No data available

ENAMEL SPRAY PAINT

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/21/2015

Revision date: 1/27/2016

Supersedes: 5/21/2015

Version: 1.0

Relative density	: No data available
Density	: 0.76 g/cm ³
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: 1.2 vol % 18.6 vol %

9.2. Other information

VOC content : 94.57 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

ENAMEL SPRAY PAINT

Vaporizer | Aerosol

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

ENAMEL SPRAY PAINT Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/21/2015

Revision date: 1/27/2016

Supersedes: 5/21/2015

Version: 1.0

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : 1950
UN-No. (ADN) : 1950
UN-No. (RID) : 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable
Proper Shipping Name (ADN) : AEROSOLS
Proper Shipping Name (RID) : AEROSOLS
Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D)
Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1
Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1
Transport document description (ADN) : UN 1950 AEROSOLS, 2.1
Transport document description (RID) : UN 1950 AEROSOLS, 2.1

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1
Danger labels (ADR) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



ENAMEL SPRAY PAINT Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/21/2015

Revision date: 1/27/2016

Supersedes: 5/21/2015

Version: 1.0

IATA

Transport hazard class(es) (IATA) : 2.1
Hazard labels (IATA) : 2.1



ADN

Transport hazard class(es) (ADN) : 2.1
Danger labels (ADN) : 2.1



RID

Transport hazard class(es) (RID) : 2.1
Danger labels (RID) : 2.1



14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : 5F
Special provisions (ADR) : 190, 327, 344, 625
Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E0
Packing instructions (ADR) : P207, LP02
Special packing provisions (ADR) : PP87, RR6, L2
Mixed packing provisions (ADR) : MP9
Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12

ENAMEL SPRAY PAINT Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/21/2015

Revision date: 1/27/2016

Supersedes: 5/21/2015

Version: 1.0

Special provisions for carriage - Operation (ADR) : S2

Tunnel restriction code (ADR) : D

- Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP02

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

MFAG-No : 126

- Air transport

PCA Excepted quantities (IATA) : E0

PCA Limited quantities (IATA) : Y203

PCA limited quantity max net quantity (IATA) : 30kgG

PCA packing instructions (IATA) : 203

PCA max net quantity (IATA) : 75kg

CAO packing instructions (IATA) : 203

CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

- Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

- Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

Limited quantities (RID) : 1L

Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP02

Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9

Transport category (RID) : 2

Special provisions for carriage – Packages (RID) : W14

Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12

Colis express (express parcels) (RID) : CE2

Hazard identification number (RID) : 23

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

ENAMEL SPRAY PAINT

Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 5/21/2015

Revision date: 1/27/2016

Supersedes: 5/21/2015

Version: 1.0

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 94.57 %

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 1, low hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : ethanol, ethyl alcohol is listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : ethanol, ethyl alcohol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : ethanol, ethyl alcohol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : ethanol, ethyl alcohol is listed

Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas	Gases under pressure
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H229	Pressurised container: May burst if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
EUH066	Repeated exposure may cause skin dryness or cracking

SDS EU AKFIX

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product