



Repairs Holes and Cracks in All ...

**HVAC/R**

Tubing and Pipes



**2 PART • 3 STEP  
INSTANT  
REPAIR**

**- COMPLETE KIT -**

**Easy as: A+B+A**

**- Complete Repair In Seconds -**

**LIFETIME PERMANENT REPAIR  
1800 PSI CONTAINED PRESSURE**

## REPAIRS HOLES AND CRACKS IN ALL **HVAC/R** TUBING AND PIPES

**Tested to 1800 psi contained air or refrigeration pressure**

Instant HVAC/R Patch is the combination of high strength bonding fluid and specialized bonding cells. The bonding fluid has an affinity for the bonding cells and when the two are combined, they form a high strength bond similar to a "weld" that permanently seals holes and cracks in all types of pipe and materials used in the HVAC/R industry.



- Works on Aluminum.
- Compatible with all refrigerant oils.
- For use on 410 systems.
- For use on coils and lines.
- Repairs leaks

Includes: Complete Bilingual Instructions.

- 1- Multi-functional Applications Tool
- 1- Part "A" Bonding Fluid with Application Tip
- 1- Part "B" Bonding Cells with Application Tip
- 2- Precision Application Brushes
- 1- 60 Grit Sanding Patch

Repairs lines, drains, coils, in copper, aluminum, stainless steel, iron, PVC, CPVC, rigid plastics, and much more.

**Easy as: A + B + A**

### STEP 1

After sanding, apply **BONDING FLUID (A)** to repair area



### STEP 2

Apply **BONDING CELLS (B)** on top of (A)



### STEP 3

Apply **BONDING FLUID (A)** on top of (B)



### SPECIFICATIONS:

- Holds 1800 psi contained pressure
- -60°F (51°C) to 200°F (93°C)
- Shore D 85+ hardness
- Non-toxic and safe to use on all potable water systems.

**WARNING!  
DO NOT INGEST.  
BONDS SKIN  
AND EYES IN  
SECONDS.**

**CAUTION: KEEP OUT OF REACH OF CHILDREN  
Read Instructions and Cautions inside  
package before using.  
Warranty limited to replacement of product.**



**HIGHSIDE**  
CHEMICALS INC.

11114 Reichold Road, Gulfport, MS 39503 U.S.A.  
1-800-359-5599 1-228-896-9220  
www.highsidechem.com

**Making the Best Chemical Tools for Over 80 Years**